

Intex BlazeBlocker® Fire Rated Sealant

PAGE 1 -3

6FR3G Intex BlazeBlocker® Fire Rated Sealant Cartridge x 300ml (10.2oz) Grey

6FR3W Intex BlazeBlocker® Fire Rated Sealant Cartridge x 300ml (10.2oz) White

6FR6G Intex BlazeBlocker® Fire Rated Sealant Sausage x 600ml (20.2oz) Grey

6FR6W Intex BlazeBlocker® Fire Rated Sealant Sausage x 600ml (20.2oz) White

Description: An acrylic fire and acoustic rated sealing compound, designed for the sealing of gaps and service penetrations in plasterboard and masonry walls, floors, and ceilings.

Composition / Information on Ingredients

Contains Contains a plasticized acrylic polymer, fire retardant fillers, blowing agents and minor additives. No component labelled as dangerous under EEC directives criteria.

Hazardous Components No hazardous components.

Hazards Identification

Main Hazards No significant hazard.

First Aid Measures (Symptoms)

Skin contact There may be mild irritation at the site of contact.
Eye Contact There may be irritation and redness.
Ingestion There may be irritation of the throat.
Inhalation There may be irritation of the throat with a feeling of tightness in the chest.

First Aid Measures (Action)

Skin contact Wash immediately with soap/cleanser and water, if symptoms persist obtain medical advice.
Eye Contact Bathe the eye with running water for 15 minutes. Seek medical attention.
Ingestion Wash out mouth with water and do not induce vomiting. Give plenty of water to drink. Seek medical attention immediately.
Inhalation Remove to fresh air and rest. Consult a doctor.

Fire Fighting Measures

Suitable Extinguishers Media for the surrounding fire should be used.
Protective equipment Do not use water jets.

Accidental Release Measures

Personal Precautions Ventilate area. Refer to Section 8 and (of the MSDS for personal protection details).
Environmental precautions Do not discharge into drains or rivers. Dispose of in accordance with local authority requirements.
Clean-up Procedures Absorb in an inert material such as sand or absorbent granules, scoop up and await transfer.

Handling & Storage

Handling Requirements Wear suitable protective clothing.
Storage conditions Store in a cool dry, well ventilated area. Store in original containers between +5 degrees C and +25 degrees C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties. See section 11 of MSDS.
Suitable packaging Must only be kept in original packaging.

Intex BlazeBlocker® Fire Rated Sealant Continued

PAGE 2 -3

Exposure Control & Personal Protection

Exposure Control	None available.
Respiratory Control	Respiratory protection not required.
Hand protection	Protective gloves.
Eye Protection	Safety glasses with side shields. Ensure eye bath is to hand.
Skin Protection	Protective clothing

Physical & Chemical Properties

State	Paste, hardening to plastic.
Colour	White, grey, brown.
Odour	Barely perceptible odour.
Evaporation Rate	Slow.
Oxidising	Non-oxidising.
Viscosity	Highly viscous.
Viscosity Value	400-600.
Viscosity Test Method	X 1000 cps – Brookfield HBDV2+, spindle S70, 10rpm@20 deg C.
Solubility In Water	Miscible in water.
Relative Density	1.6-1.65 kg/m3.
pH	8-9.5.
Other Info	VOC content <0.g/L

PRODUCT	VOC (g/L)	VOC (mg/g)	Test Reference
Intex BlazeBlocker® Fire Rated Sealant	<0.5	<0.5	254570

Stability & Reactivity

Stability	Stable under normal conditions.
Conditions to Avoid	Heat, direct sunlight, humidity.
Materials to Avoid	Strong oxidising agents. Strong acids.
Haz. Decomp. Products	None known.

Toxicological Information

Routes of Exposure	Refer to Section 4 of MSDS for routes of exposure and corresponding symptoms.
Acute Toxicity	No toxic effects known.

Ecological Information

Persistence and degradability	No data available.
Bio-accumulative potential	No data available.
Other adverse effects	No data available.

Intex BlazeBlocker® Fire Rated Sealant Continued

PAGE 3 -3

Disposal Considerations

Disposal Operations Tipping above or underground (eg landfill etc) according to local or national legislation. Do not discharge into drains or water ways.

Disposal of Packaging Dispose of as normal industrial waste according to local or national legislation.

Transport Hazards

Transport hazards No regulations apply for the transport of this material. Not classified as hazardous road, rail, sea or air transport.

Hazard Symptoms No significant hazard.

Additional Information

Risk Phrases used in s.2
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65: Harmful – may cause lung damage if swallowed.

Disclaimer The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage transportation, disposal and release and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.

Limitation

Intex Group Int. Fire & Safety have provided the above information in good faith and to the best of its knowledge. Some of this information is based upon the MSDS and technical information provided by other parties or manufacturers. This information was correct at the time of publication, should any data come to Intex Group Int. Fire & Safety's attention relating to the safety or handling of the product described, we will amend this report.

Contact In Australia: Intex Group Int : **1300 107 108** (business hours). For emergency information outside normal business hours, please ring: **1300 132 390**. The information herein is given in good faith, but subject to the Trade Practices Act 1974, no warranty, expressed or implied is made. . .
End of MSDS.